

Ceramic Fiber Gasket Twisted Rope, 2300F Rated, ½" Diameter x 25 ft, Commercial & Industrial Boiler, Furnace, Kiln Door Seal



PRODUCT INFO: Ceramic fiber rope that can withstand continuous temperatures of 2300F. Twisted ply type. Cream colored. Made from alumina-silicate based ceramic fiber.

USES: Used on commercial and industrial oil, gas and wood fired boilers, furnaces, stoves, kilns, evaporators and forges as a gasket material.

USES: Used to seal doors and access points.

DIMENSIONS: 3/8" Diameter x 25ft Long. Standard density.



Application, Installation and Use Warning:

In applications including; boilers, furnaces, wood stoves, wood inserts, fireplaces, heating devices, and other appliances, parts must be used consistently with original equipment manufacturers specifications, design, function and operation.

Improper installation or use of this product could result in a fire, smoke inhalation or carbon monoxide poisoning. Products should be installed by a licensed and certified technician in compliance with all national, state and local codes. Products should be inspected annually by a licensed and certified technician for wear, brittleness, cracking or crumbling, and replaced as necessary. Lynn Manufacturing, Inc. recommends installers certified by NFI, CSIA or NORA.

Never work on a piece of equipment or touch the fibrous product when it is hot, as the product may show no visible signs of heat from glowing or smoking.

Lynn Manufacturing, Inc offers hundreds of products with many applications. Determining whether the product is a fit for the particular purpose and suitable for an application is the sole responsibility of the purchaser/installer.

In no event shall Lynn Manufacturing, Inc be liable for any damages to property or life arising from or connected with the use of this product.

V1119