

High Temperature Gasket Rope, 1000F Rated, 3/16" Diameter x 25ft, White w/ Self Adhesive, High Density, Boiler & Furnace Door



PRODUCT INFO: White round high density rope that can withstand continuous temperatures of 1000F with self-adhesive tape.

USES: Used on oil, gas and wood fired boilers, furnaces, stoves, kilns, evaporators and forges as a gasket material. Often used to seal doors and access points. Easy to cut with a knife.

DIMENSIONS: 3/16" Diameter x 25ft Long.

DENSITY: This is a high-density rope which holds its shape under pressure, and has 50% more weight than standard density ropes



Application, Installation and Use Warning:

In applications including; boilers, furnaces, wood stoves, wood inserts, fireplaces, heating devices, and other appliances, parts must be used consistently with original equipment manufacturers specifications, design, function and operation.

Improper installation or use of this product could result in a fire, smoke inhalation or carbon monoxide poisoning. Products should be installed by a licensed and certified technician in compliance with all national, state and local codes. Products should be inspected annually by a licensed and certified technician for wear, brittleness, cracking or crumbling, and replaced as necessary. Lynn Manufacturing, Inc. recommends installers certified by NFI, CSIA or NORA.

Never work on a piece of equipment or touch the fibrous product when it is hot, as the product may show no visible signs of heat from glowing or smoking.

Lynn Manufacturing, Inc offers hundreds of products with many applications. Determining whether the product is a fit for the particular purpose and suitable for an application is the sole responsibility of the purchaser/installer.

In no event shall Lynn Manufacturing, Inc be liable for any damages to property or life arising from or connected with the use of this product.

V1119